## **Edmonton Boom Lift License**

Edmonton Boom Lift License - Just completely certified individuals should operate an aerial boom lift. Qualification could be obtained through a combination of classroom sessions and practical training with the particular kind of aerial lift that will be used on the job. A License is required for any person who works on or operates an aerial boom lift.

Vehicle-mounted aerial devices comprise the following work vehicles: extensible boom platforms, aerial ladders, articulating boom platforms, vertical towers, and whatever combination of these types.

There are some basic safety rules which apply to all boom lifts. Worker safety whilst inside the basket is a top priority. Workers should put on a body harness and lanyard connected to the boom or basket. Never tie off to an equipment, an adjacent pole or a structure. Personnel should stand on the floor of the basket, and never climb or sit on the edge of the basket. The manufacturer's load limitations should be adhered to.

Lift operators have to be certified to operate an aerial lift. The manufacturer's manual must be kept inside the lift and the operator has to know all aspects of that specific unit. Operators are responsible for making sure that safety measures are followed in the operation of the lift. Testing lift controls each day should be done. Position outriggers and set brakes (if they are used) on pads or a stable surface. When working on a slope, use wheel chocks.

Never move an aerial lift truck with an elevated boom whilst workers are within the basket. Extensible boom platforms and articulating boom made use of as employees carriers should have plainly marked, accessible, upper controls. Except for in emergency cases, lower controls should not be used to override upper controls unless permission has been given by the individual inside the lift.

While working from an aerial lift, do not wear tree or pole climbers.

The insulated portion of the aerial lift must not be altered.

Ensure that the booms are carefully checked, that the machine is properly cradled and the outriggers are in the stowed position before moving.

Make sure that lifts being utilized near or in power lines are di-electrically tested and follow local regulations.